

सूचना नं. : ३९

सूचना!

सूचना!!

सूचना!!!

प्रकाशित मिति : २०७९-०३-१७

विषय : दररेट पेश सम्बन्धमा


प्रस्तुत विषयमा यस मदन भण्डारी स्वास्थ्य विज्ञान प्रतिष्ठानलाई आउँदो शैक्षिक सत्र सञ्चालन गर्न अति आवश्यक तपशिलमा उल्लेखित सामग्रीहरु (IFB No: MBAHS/DP/003/078-79) छोटो समयमा आपूर्ति गर्न पर्ने भएको हुँदा इजाजत प्राप्त इच्छुक आपूर्ति - कर्ताहरुले यो सूचना प्रकाशित मितिले ३ दिन भित्र आवश्यक कागजातहरु संलग्न गरी दररेट पेश गर्न अनुरोध सहित यो सूचना प्रकाशित गरिएको छ ।

तपशिल

Computer Assets and IT security Equipment (IFB No: MBAHS/DP/003/078-79)

S.N.	Device	Types	Specifications	Quantity
1	Server	Rack Server with Rack, High End , Branded, HQ	2 socket, 2RU Intel, Xeon Scalable processors upto 36 cores PP, upto 3 300w GPUs, Memory 16 GB with upto 2933MT/s, Storage: upto 16 x 2.5" SAS/SATA/SSD max 122.88 TB, upto 8x3.5" SAS/SATA, with 1 GB x 2 = 2 GB SSD, 2 TB x 4 = 8TB HDD, RAID Controller RAID 2, RAID 5, S140, HWRAID 2 x M.2 SSDs 240 GB, 480 GB, cryptographically signed firmware, secure boot, secure Erase, Silicon RoT, Dual Power supply, iDRAC9, iDRAC Direct / restful API with Redfish, Quicksync 2BLE/wireless module, 4 x 10 GbE, Front ports: 2xUSB 2.0, 1xUSB 3.0, 1xVGA, 1xDedicated iDrac direct USB, Rear Ports : 1 x Dedicated iDRAC network port, 1 x serial, 2 x USB 3.0, 1 x VGA, 8xGen3 slots (4x16), 1 x VGA, with Security Bezel or LCD, 2U Rack server, with 27-35 U 600x800 server Rack	1
2	Wireless AP	Outdoor, Wide Range, Dual Band	Dual Band 2.4/5 Ghz, PoE supported Outdoor weather proof. 802.11 AC, Heating proof	1
3	Wireless AP	Indoor, Dual Band, Wide Range	Dual Band 2.4/5 Ghz, PoE supported, Indoor. 802.11 AC, Heating proof	1
4	Core Router	High End Cloud Core	High End, Dual Power supply, CPU Core – 32-48, 1.2GHz, RAM- 4 GB, Storage- 1 GB NAND, 12-G Ethernet, 4 SFP ports, Dual FAN, RJ45 Console, 1 USB, M.2 Slots – 1, minimum 1 POE inbuilt, inbuilt LCD for temperature, Voltage, MODE, Tx/Rx monitor, CE/EAC/ROHS supported with 2x power cords and dual power supported, rack ears and K-57 kit	1
5	Core Router	High End enterprise core router	ARM 32 or 64 bit, 4 core cpu @ 1.4 GHz, Memory : 512-1GB, 128 MB NAND Storage, POE In supported, poe input 20-57 V, 4-6 G-Ethernet	1
6	Switch	24 Ports, L3 Switch	24 G-Ethernet, 128 – 512 FLASH, min. 2 SFP Ports, manageable switch with extend mode	1

नोट: दररेट शिलबन्दी गरी प्रतिष्ठानको दर्ता शाखामा बुझाउन अनुरोध छ ।


बिजेन्द्र भट्टराई
प्रशासकिय अधिकृत